

EX032-A



3-Way Ultra-Compact Point-Source FOH

FEATURES

- Very high power-density
- 3-Way 4x8" LF Woofers + 3" MF CD + 1.75" HF CD
- 140 dB Peak SPL
- 3 kW Class-D Powersoft power module
- Integrated 24-bit @48kHz DPS with 4 selectable presets
- Pole-mount, flown and stacked configurations
- Rugged and durable 15/18 mm birch plywood
- Dedicated transport, installation and rigging accessories

APPLICATIONS

- Point Source FOH
- Side/Front/Drum-fill

OVERVIEW

EXO 32-A is a diminutive FOH loudspeaker, capable of delivering sufficient dynamic range and total output for Regional touring concerts and high SPL DJ gigs.

Just like the EX018, EX032 combined with BASSO Series subwoofers, allows for highly portable point source Main PA solution, but EX032 delivers such performance in an enclosure with similar overall dimensions to a 12" two way speaker.

The 3 way configuration, relies on a LF horn-loaded quad 8" cluster, a large format compression driver that takes care of a wide band of mid-range frequencies and PM4 membrane 1,75" compression driver for sizzling HF reproduction. EX032 stands out in power density and audio reproduction quality, pole mount, stacked or flown.

TECHNICAL DATA

| | |
|------------------------------|------------------------------|
| Cabinet design | Bass-reflex / Wedge |
| HF Transducers | 1 x 1.75" Compression Driver |
| MF Transducers | 1 x 3" Compression Driver |
| LF Transducers | 4 x 8" Woofers |
| Class-D Amp Continuous Power | 3000 W |
| SPL (Continuous/Peak) | 134/140 dB SPL |
| Frequency Range (-10 dB) | 70 - 21000 Hz |
| Coverage | 50° / 80° |
| Connectors | 2 x PowerCON / 2 x XLR |
| Dimensions (WxHxD) | 470 x 470 x 470 mm |
| Weight | 40 Kg |

